

### Fixed Attenuator Chip

- ◆ DC to 10 GHz
- ◆ 6 dB
- ◆ 100mW

#### Features

- High attenuation accuracy
- Small VSWR
- Ceramic chip: 96% alumina
- Laser trimmed
- Low cost-high performance

#### Model No. Description

FACXXX

XX- attenuation: \*\*dB.

XX- frequency range 06: DC to 6GHz  
 10: DC to 10GHz  
 12: DC to 12.4GHz  
 18: DC to 18GHz  
 26: DC to 26.5GHz.



#### Specifications

Frequency Range	DC to 10 GHz
Attenuation	6 dB
Attenuation Accuracy (Typical.)	±0.3 dB DC to 4 GHz + 0.5 dB 4 to 6 GHz + 0.6 dB 6 to 8 GHz + 1.0 dB 8 to 10 GHz
Nominal Impedance	50 Ohm
Rated Input Power	100mW
Operating Temperature	-55 °C to +150 °C


FREQ. RANGE (GHz)	VSWR(:1) Typical
DC to 4	1.15
4 to 6	1.20
6 to 8	1.25
8 to 10	1.40

#### Characteristic


For example the testing curves of FAC1006



#### Package Outlines



#### Recommended Layout



Note: all dimensions shown in mm