

Fixed Attenuator

- ◆ DC to 3 GHz
- ◆ 10 dB
- ◆ 50 Watt
- ◆ N Type

Features

- High Power
- High attenuation accuracy
- Small VSWR
- Low PIM



Specifications

Frequency Range	DC to 3 GHz
Attenuation	10 dB
Attenuation Accuracy	±0.5 dB over DC - 3 GHz
Nominal Impedance	50 Ohm
Average Power	50 Watt
Operating Temperature	-55 °C to +125°C
Storage Temperature	-55 °C to +125°C

Model No. Description

FATXXXXXX

X- power handling:50W.


X- connector type: SMA, N type or
SMB connector.

XX- attenuation: **dB.

XX- 03 represents type number

FREQ. RANGE (GHz)	Typical VSWR(:1)	Maximum VSWR(:1)
DC to 1	1.10	
1 to 2	1.20	
2 to 3	1.25	
DC to 3		1.30

Package Outlines



Notes:

- all dimensions shown in mm & inch
- Dimensions Tolerance ±2%
- Dimensions and specifications refer to connector type N unless otherwise specified.
- Custom designs available for other special attenuation value & accuracy

Material & Plating

Parts	Material	Plating(Micro-inch)
Body & Nut	Aluminum	Black Anodize
Contact (female & male)	QSn6.5-0.1	Gold 30
Insulator	Teflon	

AVERAGE POWER: 50W average to 25°C ambient temperature,
derated linearly to 0.5W @ 125°C.

PEAK POWER: 10KW (5μs pulse width with 0.5% duty cycle)

CONNECTOR TYPE: N