

### Fixed Attenuator

- ◆ DC to 18 GHz
- ◆ 40 dB
- ◆ 2 Watt
- ◆ SMA Stainless Steel Connectors

### Features

- High attenuation accuracy
- Small VSWR
- Stainless Steel
- Ceramic chip
- Low cost-high performance

### Model No. Description

FATXXXXXX

X- power handling: 2W or 5W.

X- connector type: SMA, N type or SMB connector.

XX- attenuation: \*\*dB.

XX- 18 represents type number



### Specifications

Frequency Range	DC to 18 GHz
Attenuation	40 dB
Attenuation Accuracy (Max.)	± 1.5 dB over DC - 18 GHz
Nominal Impedance	50 Ohm
Average Power	2 Watt
Operating Temperature	-55 °C to +125°C
Storage Temperature	-55 °C to +125°C


FREQ. RANGE (GHz)	Typical VSWR(:1)	Maximum VSWR(:1)
DC to 6	1.20	
6 to 12	1.25	
12 to 18	1.35	
DC to 18		1.40

### Material & Plating


Parts	Material	Plating(Micro-inch)
Body & Nut	Stainless Steel	Passivated
Contact (female & male)	Beryllium Copper	Gold 30
Insulator	Teflon	

### Characteristic

For example the testing curves of FAT1840S2



### Package Outlines



Package type: SMA

Note: all dimensions shown in mm & inch

**Note:**

Average power at 25°C ambient, derate linearly  
to 0.5W at 125°C

