


Description

The products are widely used in China and global 4G/5G base station, 5G network coverage, BeiDou navigation antenna, vehicle-mounted high-precision navigation (unmanned) antenna and other applications. The products have miniaturization, low-loss, wide-bandwidth, high power density, high reliability, high cost-effective and other competitive advantages.



Features:

- 3200-4200 MHz
- 0.7mm Height Profile
- High Isolation, Low Loss
- LTE Bands: 22, 42, 43
- WiMax WiBro Applications
- Surface Mountable
- Tape & Reel
- Non-conductive Surface
- RoHS Compliant
- Halogen-free
- 100% RF tested


Electrical Specifications

| Frequency | Isolation | Insertion Loss | VSWR |
|-------------------|----------------|-------------------------------|-----------------|
| <i>MHz</i> | <i>dB Min</i> | <i>dB Max</i> | <i>Max : 1</i> |
| 3200-4200 | 20 | 0.45 | 1.35 |
| Amplitude Balance | Phase Balance | Power | Operating Temp. |
| <i>dB Max</i> | <i>Degrees</i> | <i>Avg. CW Watts at 105°C</i> | <i>°C</i> |
| ± 0.45 | 90 ± 5.0 | 4 | -55 to +105 |

Notes:


1. All the above data are based on specified demo board.
2. Insertion loss: Thru board loss has been removed.

Mechanical Outline



Hybrid Coupler Pin Configuration

The HC35T03R has an orientation marker to denote Pin1. Once port one has been identified the other ports are known automatically. Please see the chart below for clarification:




| Pin | Configuration-1 | Configuration-2 | Configuration-3 | Configuration-4 |
|-----|-----------------|-----------------|-----------------|-----------------|
| 1 | Input | Isolated | Coupled | Direct |
| 2 | GND | GND | GND | GND |
| 3 | Isolated | Input | Direct | Coupled |
| 4 | Coupled | Direct | Input | Isolated |
| 5 | GND | GND | GND | GND |
| 6 | Direct | Coupled | Isolated | Input |

Typical Performance Data (@25°C)


| Frequency (MHz) | Coupling (dB) | Transmission (dB) | Insertion Loss (dB) | Isolation (dB) | Amplitude Balance (dB) | Phase (degree) | Return Loss(dB) | | | |
|-----------------|---------------|-------------------|---------------------|----------------|------------------------|----------------|-----------------|--------|--------|--------|
| | | | | | | | S11 | S22 | S33 | S44 |
| 3200 | -3.43 | -3.14 | -0.27 | -21.39 | -0.15 | 90.52 | -39.01 | -30.91 | -19.79 | -21.36 |
| 3250 | -3.39 | -3.16 | -0.27 | -21.18 | -0.12 | 90.57 | -41.02 | -31.75 | -19.38 | -21.08 |
| 3300 | -3.37 | -3.19 | -0.27 | -21.74 | -0.09 | 90.51 | -52.33 | -36.03 | -20.01 | -21.36 |
| 3350 | -3.35 | -3.21 | -0.27 | -21.50 | -0.07 | 90.57 | -42.97 | -35.09 | -19.56 | -21.10 |
| 3400 | -3.33 | -3.23 | -0.27 | -21.94 | -0.05 | 90.52 | -38.43 | -49.47 | -20.31 | -21.33 |
| 3450 | -3.32 | -3.24 | -0.27 | -21.83 | -0.04 | 90.58 | -36.24 | -39.20 | -19.80 | -21.01 |
| 3500 | -3.31 | -3.26 | -0.27 | -22.07 | -0.03 | 90.53 | -32.40 | -42.04 | -20.53 | -20.97 |
| 3550 | -3.31 | -3.27 | -0.28 | -21.87 | -0.02 | 90.61 | -32.32 | -40.50 | -20.20 | -20.61 |
| 3600 | -3.32 | -3.28 | -0.29 | -22.18 | -0.02 | 90.57 | -28.76 | -35.77 | -20.67 | -20.44 |
| 3650 | -3.32 | -3.29 | -0.29 | -21.80 | -0.01 | 90.61 | -29.61 | -38.34 | -20.47 | -20.41 |
| 3700 | -3.33 | -3.29 | -0.30 | -21.93 | -0.02 | 90.63 | -26.41 | -32.19 | -20.87 | -19.93 |
| 3750 | -3.33 | -3.29 | -0.30 | -21.77 | -0.02 | 90.68 | -27.07 | -34.32 | -20.88 | -19.93 |
| 3800 | -3.35 | -3.28 | -0.31 | -21.83 | -0.03 | 90.65 | -24.84 | -29.64 | -20.74 | -19.39 |
| 3850 | -3.36 | -3.27 | -0.30 | -21.85 | -0.04 | 90.70 | -25.21 | -32.16 | -20.85 | -19.46 |
| 3900 | -3.40 | -3.27 | -0.32 | -21.58 | -0.07 | 90.69 | -23.30 | -28.02 | -20.27 | -18.83 |
| 3950 | -3.40 | -3.24 | -0.31 | -21.72 | -0.08 | 90.82 | -23.55 | -30.93 | -20.66 | -19.02 |
| 4000 | -3.46 | -3.24 | -0.34 | -21.49 | -0.12 | 90.77 | -21.94 | -27.16 | -19.80 | -18.36 |
| 4050 | -3.47 | -3.22 | -0.33 | -21.73 | -0.13 | 90.92 | -22.08 | -29.42 | -20.56 | -18.37 |
| 4100 | -3.54 | -3.20 | -0.36 | -21.35 | -0.17 | 90.81 | -20.85 | -26.85 | -19.38 | -17.86 |
| 4150 | -3.56 | -3.17 | -0.35 | -21.72 | -0.20 | 90.96 | -21.05 | -28.60 | -20.47 | -17.86 |
| 4200 | -3.64 | -3.15 | -0.38 | -21.27 | -0.25 | 90.82 | -19.87 | -26.16 | -19.33 | -17.41 |


Power Derating Curves



Power Derating:

As the mounting interface temperature approaches the maximum continuous operating temperature, the power handling decreases to zero.

Typical Performance (-55°C,25°C,95°C,125°C: 3200-4200 MHz)


Typical Performance (-55°C,25°C,95°C,125°C: 2300-2700 MHz)


Definition of Measured Specifications

| Parameter | Definition | Mathematical Representation |
|--|--|--|
| VSWR (Voltage Standing Wave Ratio) | The impedance match of the coupler to a 50Ω system. A VSWR of 1:1 is optimal. | $VSWR = \frac{V_{max}}{V_{min}}$ Vmax = voltage maxima of a standing wave Vmin = voltage minima of a standing wave |
| Return Loss | The impedance match of the coupler to a 50Ω system. Return Loss is an alternate means to express VSWR. | $\text{Return Loss (dB)} = 20 \log \frac{VSWR + 1}{VSWR - 1}$ |
| Insertion Loss | The input power divided by the sum of the power at the two output ports. | $\text{Insertion Loss(dB)} = 10 \log \frac{P_{in}}{P_{cpl} + P_{transmission}}$ |
| Isolation | The input power divided by the power at the isolated port. | $\text{Isolation(dB)} = 10 \log \frac{P_{in}}{P_{iso}}$ |
| Phase Balance | The difference in phase angle between the two output ports. | Phase at coupled port – Phase at transmission port |
| Amplitude Balance | The power at each output divided by the average power of the two outputs. | $10 \log \frac{P_{cpl}}{\left(\frac{P_{cpl} + P_{transmission}}{2}\right)} \quad \text{or} \quad 10 \log \frac{P_{transmission}}{\left(\frac{P_{cpl} + P_{transmission}}{2}\right)}$ |


Test Method

1. Calibrating your vector network analyzer.
2. Connect the VNA 4 Port to DUT respectively.
3. Measure the data of coupling through port 1 to port 4(S41).
4. Measure the data of transmission through port 1 to port 3(S31).
5. Measure the data of isolation through port 1 to port 2(S21).
6. Measure the data of phase port 4 & port 3(port 1 feeding).
7. Measure the data of return loss port 1, port 2, port 3 & port 4.
8. According to the above data to calculate insertion loss, amplitude balance & phase.


Note:

1. When calculating insertion loss at room temperature, demo board loss should be removed from both coupling & transmission data. Please refer to the below table for demo board loss :

| Frequency Range(MHz) | Demo Board Loss (dB) @25°C |
|----------------------|----------------------------|
| 470-860 | 0.07 |
| 800-1000 | 0.10 |
| 1200-1700 | 0.15 |
| 1700-2000 | 0.15 |
| 2000-2300 | 0.20 |
| 2300-2700 | 0.25 |




Recommended PCB Layout




NOTE:

1. 50Ω line width is shown above designing.
2. Bottom side of the PCB is continuous ground plane.
3. All dimensions shown in mm [inch].

Reflow Profile



Reliability Test Flow



Reliability Test Flow

