

Data Sheet

PD1500U03W



Power Divider/Combiner

2-Way 0° 50Ω 1.0-2.0 GHz



Features

- Small Size (2×2mm DFN package)
- No need external 100 Ω resistor
- Very Low Loss
- Tight Amplitude Balance
- High Isolation
- Low VSWR
- Good Repeatability
- Tape & Reel
- Operating Temperature -40°C~105°C
- Storage Temperature -40°C~105°C
- Power handling
 - 2 Watts as a divider
 - 1 Watts as a combiner




TOP VIEW

Applications

- Wireless communications
- WLAN / WiMax
- SAT Radio
- ISM band instrument
- Information System for Automotive Safety

Notes:

1. This part has passed through 100% RF test.
2. Suggest to add Capacitors of DC Blocker between Pins (with black color) and external circuit to prevent DC signal entry to guarantee parts normal work.
3. Suggest to add a TVS Diode in parallel between Electrode (with black color) and Capacitor of DC Blocker to provide ESD protection for the product. TVS Diode use ON Semiconductor's ESD9101 is recommended.



ESD Rating

Human Body Model (HBM): Class 1 (≤ 800V) in accordance with ANSI/ESD STM 5.1 - 2001
 Machine Model (MM): Class M1 (50 to ≤ 100V) in accordance with ANSI/ESD STM 5.2 - 1999

Data Sheet

PD1500U03W

Power Divider/Combiner


2-Way 0° 50Ω 1.0-2.0 GHz



Frequency	Isolation	Input Return Loss	Output Return Loss	Insertion Loss
<i>MHz</i>	<i>dB Min</i>	<i>(dB) Min</i>	<i>(dB) Min</i>	<i>(dB)Max</i>
1000-1100	11.5	14.5	15	0.4
1100-1350	13.5	16.0	17	0.4
1350-1650	17.0	15.5	22	0.35
1650-2000	9	8	18	1.0
Phase Balance	Amplitude Balance	Power	Operating Temp.	
<i>Degrees</i>	<i>dB Max</i>	<i>Avg. CW Watts at 105°C</i>	<i>°C</i>	
±1.00	± 0.10	2	-40 to +105	
±1.00	± 0.10	2	-40 to +105	
±1.20	± 0.10	2	-40 to +105	
±1.40	± 0.10	2	-40 to +105	

Notes: 1. All the above data are based on specified demo board.
2. Insertion loss: Thru board loss has been removed




Typical Performance (-40°C, 25°C, 85°C, 125°C: 1000-2000 MHz)



Data Sheet

PD1500U03W

Power Divider/Combiner
2-Way 0° 50Ω 1.0-2.0 GHz





Data Sheet

PD1500U03W

Power Divider/Combiner

2-Way 0° 50Ω 1.0-2.0 GHz




Data Sheet

PD1500U03W

Power Divider/Combiner
2-Way 0° 50Ω 1.0-2.0 GHz



Outline Drawing




TOP VIEW


BOTTOM VIEW

SIDE VIEW

Land Pattern



Pin Out



TOP VIEW

Notes:

1. Require to add Capacitors of DC Blocker between Pins (with black color) and external circuit to prevent DC signal entry to guarantee parts normal work.
2. This part has passed through 100% RF test.

Recommended Land Pattern Top View

Notes: All dimensions show in millimeters

Pin #	Connection
1	GND
2	IN
3	GND
4	OUT
5	GND
6	OUT
Center Pad	GND