

Variable Attenuator

VAB Series

- ◆ DC to 2.7GHz
- ◆ 0 to 31 dB in 1 dB Step
- ◆ 2 Watt or 5 Watt
- ◆ SMA Connectors, N type, BNC available



Features

- Ultra small size with innovative microstrip technology
- Available step value:0~31dB.
- High accuracy
- High performance low cost
- Impedance: 50 or 75 ohm
- Operation repeatability:10000 times each switch
- POM material in rotary switch,operating up to 85°C
- Smart size

Specifications

| | |
|-----------------------|-----------------------------------|
| Frequency Range | DC to 2.7GHz |
| Attenuation | 0 to 31dB |
| Step Value | 1 dB |
| Insertion loss at 0dB | 0.3dB at 2GHz 0.65dB at 2.7GHz |

Attenuation Accuracy (typical)
-0.5 to +1dB from DC to 2.7GHz


| | |
|-----------------------|----------------|
| Nominal Impedance | 50 Ohm |
| Average Power | 5 Watt |
| Operating Temperature | -40°C to +85°C |

Attenuation 0~31dB


| Freq. Range (GHz) | VSWR(:1) | |
|----------------------|----------|------|
| | Typ. | Max. |
| DC to 2.7 | 1.15 | 1.30 |

Characteristic


For example the testing curves of VAB3101S5* of 31dB



Package Outlines
SMA Connector Units:mm(inch)



Mounting holes



NOTE:

1. ALL dimensions shown in mm(tolerance: +/-0.2mm) unless stated otherwise
2. RoHS Compliant in accordance with EU Directive(2011/65/EU)

Application case:

Repeater: In deploying the indoor repeater system, Rotary Variable Attenuator is ideal to control the signal and keep each repeater in its specific coverage range.

This VAB series can be rack mountable, easier to operate from the rack outside.

Application